



Version

X-HIPRO 548E-6 + JIB 150X-6

M _{dyn}		433 690 ft-lbs
Lifting capacity	ft-lbs	314 960
Lifting capacity	ft-lbs	314 853' 2"
Lifting capacity (ADC)	ft-lbs	340 720
Lifting capacity (ADC)	ft-lbs	340 602' 8"
Outreach - lifting capacity, standard	ft-lbs.	61' 4" - 2 340 65' 7" - 2 120 69' 11" - 1 920 74' 6" - 1 760 79' 5" - 1 610 85' 0" - 1 480 90' 7" - 1 390
Outreach - lifting capacity, manual extensions	ft-lbs.	95' 2" - 1 230
Hydraulic outreach, standard	ft	90' 7"
Hydraulic boom extension	ft	65' 3" ft
Outreach, manual extensions	ft	0' 0"
Lifting height above installation level, hydr/man	ft	98' 5" / 103' 4"
Rec. oil flow	gallon/min	26 - 32
Power needed at rec. oil flow V80	hp	-
Power needed at rec. oil flow V91	hp	-
Working pressure	psi	5 370
Oil in tank	gallon	53 - 79
Tank capacity	gallon	0 - 90
Slewing angle	°	999
Max slope viable at full capacity	°	5
Slewing torque, gross	ft-lbs	36 878' 1"
Slewing speed 80	°/s	8
Slewing speed	°/s	8
Lifting speed at standard hydraulic outreach	ft/s	3' 8"
Height in folded position	"	104
Width in folded position	"	99
Install space required. Rotation area not included	"	76
Install space required with hose and pipe kit	"	76
Weight		
Crane in standard version without support legs	lbs.	13 830
Top seat	lbs.	0
Frame attachments	lbs.	160 - 250
Support leg equipment	lbs.	1 880 - 2 360

Data sheet

X-HIPRO 548E-6 + JIB 150X-6