



Version

X-HIPRO 638E-6 + JIB 150X -6

| | | |
|--|------------|--|
| M _{dyn} | | 522 190 ft-lbs |
| Lifting capacity | ft-lbs | 360 690 |
| Lifting capacity | ft-lbs | 360 565' 10" |
| Lifting capacity (ADC) | ft-lbs | 390 140 |
| Lifting capacity (ADC) | ft-lbs | 390 004' 2" |
| Outreach - lifting capacity, standard | ft-lbs. | 62' 8" - 2 910 66' 11" - 2 650 71' 2" - 2 430 75' 9" - 2 250 80' 9" - 2 070 86' 3" - 1 920 91' 10" - 1 790 |
| Outreach - lifting capacity, manual extensions | ft-lbs. | 96' 9" - 1 630 |
| Hydraulic outreach, standard | ft | 92' 2" |
| Hydraulic boom extension | ft | 65' 3" ft |
| Outreach, manual extensions | ft | 0' 0" |
| Lifting height above installation level, hydr/man | ft | 99' 9" / 104' 8" |
| Rec. oil flow | gallon/min | 26 - 32 |
| Power needed at rec. oil flow V80 | hp | - |
| Power needed at rec. oil flow V91 | hp | - |
| Working pressure | psi | 5 510 |
| Oil in tank | gallon | 53 - 79 |
| Tank capacity | gallon | 0 - 90 |
| Slewing angle | ° | 999 |
| Max slope viable at full capacity | ° | 4 |
| Slewing torque, gross | ft-lbs | 36 878' 1" |
| Slewing speed 80 | °/s | 8 |
| Slewing speed | °/s | 8 |
| Lifting speed at standard hydraulic outreach | ft/s | 3' 10" |
| Height in folded position | " | 105 |
| Width in folded position | " | 100 |
| Install space required. Rotation area not included | " | 79 |
| Install space required with hose and pipe kit | " | 79 |
| Weight | | |
| Crane in standard version without support legs | lbs. | 15 220 |
| Top seat | lbs. | 0 |
| Frame attachments | lbs. | 170 - 270 |
| Support leg equipment | lbs. | 2 240 - 2 840 |

Data sheet

X-HIPRO 638E-6 + JIB 150X -6